



- 1) APPROVED ASSEMBLIES ARE REQUIRED TO HAVE RESILIENT SEATED SHUT-OFF VALVES AND TEST COCKS AS INTEGRAL PARTS OF THE ASSEMBLIES OTHERWISE THE APPROVAL IS VOIDED.
- 2) ASSEMBLY MUST BE ACCESSIBLE FOR TESTING AND MAINTENANCE.
- 3) PROTECTION FROM FREEZE DAMAGE MAY BE REQUIRED IN EXPOSED AREAS.
- 4) NO CONNECTIONS OR TEES WILL BE ALLOWED BETWEEN SERVICE CONNECTION AND ASSEMBLY.
- 5) INSTALLATION AND OPERATION MUST COMPLY WITH STANDARDS SET FORTH BY A.W.W.A. AND ALL FEDERAL, STATE, AND LOCAL LAWS, RULES, REGULATIONS, ORDERS, CODES, AND ORDINANCES.
- 6) THE DCDA SHALL BE INSTALLED AS CLOSE TO THE PROPERTY LINE AS PRACTICAL. ANY DEVIATION FROM THIS METHOD MUST BE APPROVED BY CLWSC PRIOR TO INSTALLATION.
- 7) ASSEMBLY MAY BE INSTALLED BELOW GRADE WITH APPROVAL BY CLWSC.

GENERAL NOTES:  
 (1) FOR ADDITIONAL INFORMATION, SEE CANYON LAKE WATER SERVICE COMPANY'S STANDARD SPECIFICATIONS.  
 (2) A LIST OF APPROVED DCDA'S ARE AVAILABLE UPON REQUEST.

BY	REVISION	DATE	CK	AP	OPS

**CLWSC**  
 CANYON LAKE  
 WATER SERVICE COMPANY  
 1399 Sattler Road  
 Canyon Lake, Texas 78133  
 (830) 964-3854

**APPROVED  
 DOUBLE CHECK DETECTOR  
 ASSEMBLY (DCDA) INSTALLATION**

BY: P.J./JW / MH	OPERATIONS / DATE
DATE: 04-29-10	
CK: _____	ENGINEERING / DATE
SCALE: NONE	DIRECTOR OF ENGINEERING / DATE

REF. NOS.	DWG. NO.
	<b>BK-DCDA</b>
	SHEET: 1 OF 1